电镀不锈钢精密轴 Chrome Plated Stainless Piston Rod

<table>
<tr><th>直径
Diameter</th><th>电镀层厚度
Chrome Layer Thickness</th><th>直径公差
Tolerance</th><th>圆度
Roundness</th><th>直线度
Straightness</th><th>标准长度
Standard Length</th><th>表面粗糙度
Surface Roughness</th></tr>
<tr><td>Φ3 ~ Φ25</td><td>Φ ≤ 25mm: Min. 15μm</td><td rowspan="6">公差可以按照
客户需求订制
ISO f7,f8 / other, On Request</td><td rowspan="6">≤ 1/2 直径公差
≤ 1/2 Diameter Tolerance</td><td>0.2mm/m</td><td>2m, 3m</td><td rowspan="6">Ra ≤ 0.2</td></tr>
<tr><td>Φ25 ~ Φ40</td><td rowspan="5">Φ>25mm: Min. 20μm</td><td>0.2mm/m</td><td>3m, 6m</td></tr>
<tr><td>Φ40~Φ80</td><td>0.2mm/m</td><td>3m, 6m</td></tr>
<tr><td>Φ80~Φ150</td><td>0.15mm/m</td><td>3m, 6m</td></tr>
<tr><td>Φ150~Φ200</td><td>≤0.15mm/m</td><td>3m, 6m</td></tr>
<tr><td>Φ200~Φ300</td><td>≤0.15mm/m</td><td>3m, 6m</td></tr>
<tr><td rowspan="2">其他要求
Other Requirement</td><td>电镀层厚度
Chrome Layer Thickness</td><td>镀层硬度
Chrome Layer Hardness</td><td>定制尺寸
Customized Size</td><td>定尺切割
Fixed Cut</td><td>交货状态
Delivery Condition</td><td>机加工
Machining</td></tr>
<tr><td>电镀层按照客户要求
Chrome layer thickness is according to Customers' Requirement</td><td>HV850~HV1050</td><td>英标，美标，客户要求
feet, Customers' requirement</td><td>可以定尺切割
On request we can offer cut to fixed lengths pieces</td><td>按客户要求
Customers' requirement</td><td>按客户要求
Customers' requirement</td></tr>
<tr><td colspan="7">备注： 不锈钢电镀镀层可以根据客户的要求来选择的相应的厚度。材料牌号选择请参照第五页。
Note: Stainless Steel Chrome Layer Thickness can be selected according to customers' requirement. Please Check Materials Grade Reference is on Page 5.</td></tr>
</table>