

不锈钢气缸管



Stainless Steel Cylinder Tube

不锈钢气缸管

材料 Material Grade	内径 Inner Diameter	外径 Outer Diameter	壁厚 Wall Thickness	内径公差 Tolerance	标准长度 Standard Length	直线度 Straightness	内孔表面粗糙度 Inner Surface Roughness
SUS316L	6	7	0.5	0~0.04	2500	1.5mm/m	Ra ≤ 0.4
SUS316L	8	9	0.5	0~0.04	2500	1.5mm/m	Ra ≤ 0.4
SUS316L	10	11	0.5	0~0.04	2500	1.2mm/m	Ra ≤ 0.4
SUS316L	12	13.4	0.7	0~0.05	2500	1.2mm/m	Ra ≤ 0.4
SUS316L	16	17.4	0.7	0~0.05	2500	1mm/m	Ra ≤ 0.4
SUS316L	16	18	1	0~0.05	2500	1mm/m	Ra ≤ 0.4
SUS316L	20	21.4	0.7	0~0.06	2500	1mm/m	Ra ≤ 0.4
SUS316L	25	26.4	0.7	0~0.06	2500	1mm/m	Ra ≤ 0.4
SUS316L	30	31.4	0.7	0~0.06	2500	1mm/m	Ra ≤ 0.4
SUS316L	32	33.6	0.8	0~0.07	2500	1mm/m	Ra ≤ 0.4
SUS316L	40	41.6	0.8	0~0.07	2500	1mm/m	Ra ≤ 0.4
SUS316L	50	52	1	0~0.07	2500	1mm/m	Ra ≤ 0.4
SUS316L	63	65	1	0~0.07	2500	1mm/m	Ra ≤ 0.4
SUS316L	63	65.4	1.2	0~0.07	2140	1mm/m	Ra ≤ 0.4
SUS304	63	69	3	0~0.07	2000	0.15mm/m	Ra ≤ 0.4
SUS304	80	87	3.5	0~0.07	2000	0.15mm/m	Ra ≤ 0.4
SUS304	100	106	3	0~0.08	2000	0.15mm/m	Ra ≤ 0.4
SUS304	125	133	4	0~0.08	2000	0.15mm/m	Ra ≤ 0.4
SUS304	160	170	5	0~0.1	2000	0.2mm/m	Ra ≤ 0.4
SUS304	200	213	6.5	0~0.1	2000	0.25mm/m	Ra ≤ 0.4
备注：可以根据客户的要求订制。 Note: Can be customized according to customer requirements.							