

牌号	UNS (美国)	AISI (美国)	DIN (德国)	EN (欧洲)	GB (中国)
304	S30400	304	1.4301	X5CrNi18-10	06Cr19Ni10
310s	S31008	310S	1.4845	X8CrNi25-21	0Cr25Ni20
316L	S31603	316L	1.4404	X2CrNiMo17-12-2	00Cr17Ni14Mo2
321	S32100	321	1.4541	X6CrNiTi18-10	0Cr18Ni10Ti
2205	S32205	2205	1.4462	X2CrNiMoN22-5-3	022Cr23Ni5Mo3N
254SMo	S31254	254SMo	1.4547	X1CrNiMoCuN20-18-7	015Cr20Ni18Mo6CuN



内径 Inner Diameter	外径 Outer Diameter	壁厚 Wall Thickness	内径 Inner Diameter	外径 Outer Diameter	壁厚 Wall Thickness	内径 Inner Diameter	外径 Outer Diameter	壁厚 Wall Thickness
40	50	5	155	180	12.5	200	219	9.5
40	55	7.5	155	185	15	200	225	12.5
40	63	11.5	165	180	7.5	200	230	15
40	70	15	165	185	10	200	235	17.5
50	57	3.5	165	190	12.5	200	240	20
50	60	5	165	194	14.5	200	245	22.5
50	65	7.5	165	200	17.5	200	250	25
63	70	3.5	170	180	5	200	255	27.5
63	73	5	170	185	7.5	210	230	10
63	76	6.5	170	190	10	210	235	12.5
63	83	10	170	194	12	210	240	15
63	85	11	170	200	15	210	245	17.5
80	89	4.5	170	203	16.5	210	250	20
80	92	6	175	190	7.5	210	255	22.5
80	95	7.5	175	194	9.5	210	273	31.5
80	102	11	175	200	12.5	220	240	10
100	110	5	175	203	14	220	245	12.5
100	114	7	175	205	15	220	250	15
100	121	10.5	175	210	17.5	220	255	17.5
100	127	13.5	180	194	7	220	273	26.5
125	140	7.5	180	200	10	230	250	10
125	146	10.5	180	203	11.5	230	255	12.5
125	152	13.5	180	205	12.5	230	273	21.5
130	140	5	180	210	15	230	280	25
130	146	8	180	219	19.5	240	273	16.5
130	152	11	180	225	22.5	240	280	20
135	146	5.5	185	200	7.5	240	299	29.5
135	150	7.5	185	203	9	250	273	11.5
135	152	8.5	185	205	10	250	280	15
135	159	12	185	210	12.5	250	299	24.5
140	159	9.5	185	219	17	260	280	10
140	162	11	185	225	20	260	299	19.5
140	168	14	185	230	22.5	275	299	12
145	159	7	190	210	10	275	310	17.5
145	162	8.5	190	219	14.5	275	325	25
145	168	11.5	190	225	17.5	280	310	15
148	168	10	190	230	20	280	325	22.5
150	159	4.5	190	235	22.5	280	356	38
150	162	6	195	219	12	290	325	17.5
150	168	9	195	225	15	290	356	33
150	175	12.5	195	230	17.5	300	325	12.5
150	180	15	195	235	20	300	356	28
155	168	6.5	195	240	22.5	310	356	23
155	175	10	195	245	25	310	356	23

备注：不锈钢油缸管内径要求都是按照客户的要求定制的，如果对外表光洁度要求比较高，外表面可以研磨加工。
Note:The tolerance requirements for the inner diameter of stainless steel oil cylinder tubes are customized based on customer specifications. For applications demanding high surface smoothness, the external surface can undergo precision grinding.